

W. R. GRACE
MATERIAL SAFETY DATA SHEET

Product Name: Z-3306 White/Grey
MSDS ID Number: Z-01752

MSDS Date: 07/11/2008

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Monokote Z-3306 White/Grey
MSDS Number: Z-01752
Cancelled MSDS Number: Z-01730
MSDS Date: 07/11/2008
Chemical Family Name: Cementitious Mixture.
Product Use: Thermal Barrier
Chemical Formula: Blend of Portland Cement, Clay, Cellulose & Chopped Glass Filament.
CAS # (Chemical Abstracts Service Number): Mixture-NA

Manufactured by:

W.R.Grace & Co.-Conn.
62 Whittemore Avenue
Cambridge, MA 02140

Grace Canada, Inc.
294 Clements Road West
Ajax, Ontario L1S 3C6

In Case of Emergency Call:

In USA: (617) 876-1400 In Canada: (905) 683-8561

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS#	Percent (max)
Fuller's earth	008031-18-3	1-10
Chopped continuous glass filament	065997-17-3	1-10
Polystyrene	009003-53-6	1-10
Portland cement	065997-15-1	50-100
Pulp, cellulose	065996-61-4	1-10
Quartz	014808-60-7	< 1

SECTION 3 - HAZARDS IDENTIFICATION

Emergency Overview:

Warning!

Irritating to eyes, skin and respiratory system.
Prolonged exposure may cause alkali burns resulting in damage to skin and eyes.
Prolonged exposure may cause risk of lung disease (i.e. silicosis and/or lung cancer)

HMIS Rating:

Health: 2*
Flammability: 0
Reactivity: 0
Personal Protective Equipment: E (See Section 8)

Potential Health Effects:

Inhalation: Causes respiratory tract irritation.

Exposure may aggravate chronic respiratory conditions such as asthma or bronchitis. Long-term inhalation of dust may increase risk of contracting pneumoconiosis ("dusty lungs") and reduced pulmonary function.

Prolonged inhalation of respirable crystalline silica dust can result in lung disease (i.e. silicosis and/or lung cancer). Symptoms include coughing, shortness of breath, wheezing and reduced pulmonary function.

Eye Contact: Eye contact causes irritation.

Prolonged contact may cause burns due to the alkaline nature of cement.

Direct contact with Monokote spray may cause physical injury.

Skin Contact: Skin contact causes irritation.

Prolonged skin contact causes burns especially if skin or product is wet. This may occur without warning since little heat is sensed.

Prolonged skin contact can result in permanent damage.

May cause sensitization due to Hexavalent chromium contained in Portland Cement.

W. R. GRACE
MATERIAL SAFETY DATA SHEET

Product Name: Z-3306 White/Grey

MSDS ID Number: Z-01752

MSDS Date: 07/11/2008

Exposure to skin may produce "cement" dermatitis which is due to the alkaline and abrasive properties of cement dust.

Skin Absorption: Not expected to be harmful if absorbed through the skin.

Ingestion: If ingested, causes irritation or burns to the linings of the mouth, esophagus and stomach.

SECTION 4 - FIRST AID MEASURES:

Skin Contact: Wash with soap and water.

If discomfort or irritation persists, consult a physician.

Remove contaminated clothing and wash before reuse.

Eye Contact: Flush eyes with water for at least 15 minutes while holding eyelids open.

Get immediate medical attention.

Ingestion: Do not induce vomiting.

Never give anything by mouth to an unconscious person.

If discomfort or irritation persists, consult a physician.

Inhalation: If symptoms develop, get fresh air. If symptoms persist, consult a physician.

If breathing has stopped, give artificial respiration then oxygen if needed.

SECTION 5 - FIRE AND EXPLOSION HAZARD DATA

Flash Point: Not Applicable

Flash Point Method: Not Applicable

Lower Explosion Limit: Not Available

Upper Explosion Limit: Not Available

Auto-Ignition Temperature: Not Available

NFPA Rating:

Health: 2

Flammability: 0

Reactivity: 0

Extinguishing Media: Not Applicable. Product will not burn.

Special Fire Fighting Procedures: None

No special procedures specific to this product.

Unusual Fire and Explosion Hazards: None unless noted below.

SECTION 6 - ACCIDENTAL RELEASE MEASURES:

Spills/Leaks: If spilled, prevent material from entering water systems. Observing the listed Precautionary Measures found in Section 7 of this document. Dry spills should be immediately swept up and placed in a suitable container to prevent further release of material. Slurry spills should be immediately contained (to minimize the extent of the spill) and absorbed with an inert, non-combustible material. Place material in a suitable container to prevent further release.

Use proper personal protective equipment. Do not flush to sewer or allow to enter waterways.

SECTION 7 - HANDLING AND STORAGE

Precautionary Measures:

Avoid contact with eyes, skin and clothing.

Wear skin and eye protection to avoid contact with dust or spray.

Avoid creating and inhaling airborne dust or particulates.

Practice good personal hygiene to avoid ingestion.

Use only with adequate ventilation.

Wash clothing before reuse.

Equip mixers with dust covers.

Provide respiratory protection if needed.

Wear skin and eye protection to avoid contact with dust or spray.

Post "Slippery When Wet" signs where appropriate.

Use anti-slip surfaces on working platforms.

FOR PROFESSIONAL USE ONLY. KEEP OUT OF CHILDREN'S REACH.

W. R. GRACE
MATERIAL SAFETY DATA SHEET

Product Name: Z-3306 White/Grey
MSDS ID Number: Z-01752

MSDS Date: 07/11/2008

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTIVE EQUIPMENT

EXPOSURE GUIDELINES (US)

Ingredient	ACGIH TLV			OSHA PEL			Other
	TWA	STEL	Ceiling	TWA	STEL	Ceiling	
Fuller's earth	-	-	-	-	-	-	-
Chopped continuous glass filament	-	-	-	-	-	-	-
Polystyrene	-	-	-	-	-	-	-
Portland cement	10 mg/m ³ TWA (particulate matter containing no asbestos and < 1% crystalline silica)	-	-	10 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction)	-	-	-
Pulp, cellulose	-	-	-	-	-	-	-
Quartz	0.025 mg/m ³ TWA (respirable fraction)	-	-	((250)/(%SiO ₂ + 5) mppcf TWA (respirable)); (10)/(%SiO ₂ + 2) mg/m ³ TWA (respirable); (30)/(%SiO ₂ + 2) mg/m ³ TWA (total dust)	-	-	-
Vinyl Acetate Polymer	-	-	-	-	-	-	-

In addition to the exposure limits referenced above, the following non-specific limits for dust apply to this product; OSHA, 15 mg/m³-TWA or Total Dust and 5 mg/m³-TWA as Respirable Dust, ACGIH, 10 mg/m³-TWA as Total Dust and 3 mg/m³-TWA as Respirable Dust.

EXPOSURE GUIDELINES (CANADA)

Employers should consult local Provincial regulatory limits for exposure guidelines which may vary locally.

Engineering Controls: Exhaust fans may be necessary when mixing in enclosed areas.

Personal Protective Equipment:

Respiratory Protection: Wear approved respiratory protection (generally a N-95 dust mask) to prevent employee exposure from exceeding the limits specified.

Skin Protection: Work gloves or hand creams are recommended to prevent drying of skin.

Eye Protection: At minimum, safety glasses with side shields should be worn where exposure to excessive dust or spray is likely.

Work/Hygienic Practices: Use good personal hygiene practices.

Use bag opening and disposal procedures which minimize dust release. Equip mixers with dust covers to minimize dust released during mixing cycle. After each work shift, workers should shower with soap and water. Work clothing should be changed daily.

Prior to welding or cutting, product must be removed from steel surfaces in those immediate areas where exposure to excessive heat, applied either directly or through conduction, from cutting or welding operations is possible.

Remove material in a manner so as to minimize the creation of dust. All trades should minimize the release of dust during removal of materials by:

- Applying a spray mist of water to wet product, prior to its removal.
- Removing small areas of fireproofing at one time.
- Maintaining a clean worksite.

Quartz (Crystalline silica) is a naturally-occurring mineral that is commonly contained in materials that are mined from the earth's surface such as sand, limestone, clay and gypsum (Calcium sulfate). Total quartz is a value usually representing the combined fractions of large, nonrespirable sized particles and of respirable sized particles (less than ten microns in aerodynamic diameter). It is only the respirable fraction of total quartz that is recognized as hazardous by professionals in the field of Occupational Health and by most regulatory agencies. Clay contained in this product may contain very small particles which might be described as microfibrinous (0.02-0.1 Åm diameter and 0.1-2.5 Åm in length with a mean particle length of 0.4 Åm). These particles are not regulated. Studies to date show that these particles are not fibrogenic nor carcinogenic and unlikely to cause pulmonary dysfunction. Portland Cement may contain trace amounts of heavy metals recognized as carcinogens by NTP, OSHA or IARC.

W. R. GRACE
MATERIAL SAFETY DATA SHEET

Product Name: Z-3306 White/Grey
MSDS ID Number: Z-01752

MSDS Date: 07/11/2008

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Solid
Appearance/Odor:	Coarse, free flowing white to grey powder, no odor.
Odor Threshold: (ppm)	Not Available
pH:	11 - 13
Vapor Pressure: (Mm Hg)	Not Applicable
Vapor Density: (Air = 1)	Unknown
Solubility In Water:	Slight
Specific Gravity: (Water = 1)	Not Applicable
Evaporation Rate: (Butyl Acetate = 1)	Not Applicable
Boiling Point:	Not Applicable
Viscosity:	Unknown
Bulk Density: (Pounds/Cubic Foot)(Pcf)	17 - 25
% Volatiles (gr/L): (70°F) (21°C)	Not Applicable

SECTION 10 - STABILITY AND REACTIVITY

Chemical Stability:	Stable
Conditions To Avoid:	Polyunsaturated liquids.
Hazardous Polymerization:	Will not polymerize.
Hazardous Decomposition Products:	Carbon dioxide, Carbon monoxide, Monomers (C8H8) and various polymers (C8H8). Temperatures in excess of 4000°F from cutting or welding operations may generate Sulfur dioxide. Upon complete combustion, Carbon monoxide and Carbon dioxide are released and trace amounts of nitrogen and asphyxiants.

SECTION 11 - TOXICOLOGICAL INFORMATION

Ingredient(No data unless listed.)	CAS Number	LD50 and LC50
Carcinogenicity:		

Ingredient	IARC Group 1	IARC Group 2A	IARC Group 2B	NTP Known	NTP Suspect	OSHA
Fuller's earth	No	No	No	No	No	No
Chopped continuous glass filament	No	No	No	No	No	No
Polystyrene	No	No	No	No	No	No
Portland cement	No	No	No	No	No	No
Pulp, cellulose	No	No	No	No	No	No
Quartz	Yes	No	No	Yes	No	Yes
Vinyl Acetate Polymer	No	No	No	No	No	No

Mutagenicity:	Not applicable.
Teratogenicity:	Not applicable.
Reproductive Toxicity:	Not applicable.

SECTION 12 - ECOLOGICAL INFORMATION

Environmental Fate:	No data available for product.
Ecotoxicity:	No data available for product.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal Procedures: Consult all regulations (federal, state, provincial, local) or a qualified waste disposal firm when characterizing waste for disposal. According to EPA (40 CFR § 261), waste of this product is not defined as hazardous. Dispose of waste in accordance with all applicable regulations. Wastes of this product such as empty bags and excess material are typically not defined as hazardous.

SECTION 14 - TRANSPORTATION INFORMATION

Proper Shipping Name:	Not Applicable
UN/NA Number:	Not Applicable
Domestic Hazard Class:	Nonhazardous
Surface Freight Classification:	Not Applicable
Label/Placard Required:	Not Applicable

